

## Features

The P3000 delivers 1,800 watts per channel at two ohms. Neutrik Speakon® output connectors allow use of heavy-gauge speaker wire for low-loss connections. Extremely low dynamic distortion ensures excellent sound quality. Three-rack spaces.

## Specifications

Continuous rated power (1k Hz, THD 1%) 2Ω	1800 Watts
Continuous rated power (1k Hz, THD 1%) 4Ω	1300 Watts
Input Impedance (balanced)	20 kΩ
Continuous rated power (1k Hz, THD 1%) 8Ω	850 Watts
Continuous rated power (20-20k Hz, THD<0,2%) 4Ω	1200 Watts
Continuous rated power (20-20k Hz, THD<0,2%) 8Ω	750 Watts
Maximum bridged output 4Ω	3600 Watts
Maximum bridged output 8Ω	2600 Watts
Slew Rate	> 40 V / μs
Electronics Type	Amplifier
Network Control (IRIS-Net)	No
Total harmonic distortion	< 0.05 %
Intermodulation Distortion (SMTPE)	< 0.01 %
DIM 30	< 0.01 %
Signal-to-noise ratio (A-weighted)	> 105 dB
Input Sensitivity	0 dBu / +6 dBu / +26 dB
Weight Net	29 kg ( 63.93 lbs )
Dimensions (HxWxD)	133 x 483 x 390 mm (5.24" x 19.02" x 15.35")